


GigaCore 16RFO



Gigabit Ethernet Switch for the entertainment industry

Quick Start Guide

V2.1.0

Rev3

English

Table of Content

■	Safety Instructions	3
■	Compliance information	4
■	Warranty information	5
■	Registration	5
■	In the box	5
■	Description	6
■	Starting	10
■	Connection to the web interface	11
■	Additional documentation	11

GigaCore 16RFO Quick Start Guide

Document lu_01_00056_qsg_rev3

Copyright © 2002-2016 .

All rights reserved.

No part of this documentation may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, without the prior written permission of Luminex.

The information in this documentation is supplied without warranty of any kind, either directly or indirectly, and is subject to change without prior written notice. Luminex, its employees or appointed representatives will not be held responsible for any damages to software, hardware, or data, howsoever arising as a direct or indirect result of the product(s) mentioned herein.

Issued by:

Publications Department,

Luminex LCE, Berkenlaan 8A, Hechtel Eksel, B-3940, Belgium.

Documentation last reviewed 11 January 2016 by Luminex LCE.

Printed in the EU.

Safety Instructions

	CAUTION Risk of electric shock Do not open !
	ATTENTION Risque de choc électrique Ne pas ouvrir !



CAUTION: TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE THE COVER. NO USER SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.



WARNING: TO REDUCE THE RISK OF FIRE OR ELECTRIC SHOCK, DO NOT EXPOSE THIS APPLIANCE TO RAIN OR MOISTURE.




The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.



The lightning flash with arrowhead symbol, within an equilateral triangle, is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.

- Read Instructions - All the safety and operating instructions should be read before the appliance is operated.
- Retain Instructions - The safety and operating instructions should be retained for future reference.
- Heed Warnings - All warnings on the appliance in the operating instructions should be adhered to.
- Follow Instructions - All operating and user instructions should be followed.
- Water and Moisture - The appliance should not be used near water; for example, near a fountain, or submitted to direct water exposure.
- The apparatus shall not be exposed to dripping or splashing liquids and no objects filled with liquids, such as bottles, shall be placed on the apparatus. Do not touch the appliance with wet hands. Do not handle the appliance or power cord with wet or damp hands. If water or any other liquid enters the appliance cabinet, take it to qualified service personnel for inspection.
- Cleaning - The appliance should be cleaned only as recommended by the manufacturer. From time to time you should wipe off the front and side panels and the enclosure with a soft cloth. Do not use rough material, thinners, alcohol or other chemical solvents or cloths since this may damage the finish or remove the panel lettering.
- Ventilation - The appliance should be situated so that its location or position does not interfere with its proper ventilation. Place the unit in a well-ventilated location, leaving at least 5 cm (2 inches) of clearance on front, side and rear of unit for air flow. If ventilation is blocked, the unit may overheat and malfunction.
- Heat - The appliance should be situated away from heat sources such as radiators or heating systems.
- Power Cord Protection - Power supply cords should be routed so that they are not likely to be walked on or pinched by items placed upon or against them, paying particular attention to cords at plugs, receptacles, and the point where they exit from the appliance.
- Power Sources - The appliance should be connected to a power supply only of the type described in the operating instructions or as marked on the appliance.
- Attachments / Options - Only use attachments/options specified by the manufacturer.
- Object and Liquid Entry - Care should be taken so that objects do not fall and liquids are not spilled into the enclosure through the openings.
- Servicing - The user should not attempt to service the appliance beyond that described in the operating instructions. All other servicing should be referred to qualified service personnel.
- Damage Requiring Service - The appliance should be serviced by qualified service personnel when: A. The power supply cord or the inlet has been damaged; B. Objects have fallen, liquid has been spilled into the appliance; C. The appliance has been exposed to rain; or D. The appliance does not appear to operate normally; or E. The appliance has been dropped or the enclosure is damaged.
- The equipment shall be used at a maximum ambient temperature of 50° C / 140° F.

Disposal of Waste Equipment by users in the European Union



This symbol on the product or its packaging indicates that this product must not be disposed of with other waste. Instead, it is your responsibility to dispose of your waste equipment by handing it over to a designated collection point for the recycling of waste electrical and electronic equipment. The separate collection and recycling of your waste equipment at the time of disposal will help conserve natural resources and ensure that it is recycled in a manner that protects human health and the environment. For more information about where you can drop off your waste equipment for recycling, please contact your local city recycling office or the dealer from whom you purchased the product.

EMC (Electromagnetic Compliance)

This model GigaCore 16RFO complies with the following standards regulating interference and EMC:

- EN 55103-1, environment E2
- EN 55103-2, environment E2

CE Compliance (EMC and Safety)



Luminex is authorized to apply the CE mark on this compliant equipment thereby declaring conformity to EMC Directive 2004/108/EC and Low Voltage Directive 2006/95/EC.

Warranty information

Limited warranty

Unless otherwise stated, your product is covered by a two (2) years parts and labor limited warranty. It is the owner's responsibility to furnish receipts or invoices for verification of purchase, date, and dealer or distributor. If purchase date cannot be provided, date of manufacture will be used to determine warranty period.

Returning under warranty

Any Product unit or parts returned to Luminex LCE must be packaged in a suitable manner to ensure the protection of such product unit or parts, and such package shall be clearly and prominently marked to indicate that the package contains returned product units or parts. Accompany all returned product units or parts with a written explanation of the alleged problem or malfunction.

Freight

All shipping will be paid by the purchaser. Items under warranty shall have return shipping paid by the manufacturer only in the European Union.

Under no circumstances will freight collect shipments be accepted. Prepaid shipping does not include rush expediting such as air freight. Air freight can be sent customer collect in the European Union.

Warranty is void if the product is misused, damaged, modified in any way, or for unauthorized repairs or parts.

Registration

Use your favorite web browser, and visit <http://www.luminex.be/support.php?show=registration> to register your product online.

By registering, you become eligible to receive the following:

- Technical support information
- Software update and upgrade notices
- Hardware warranty information

In the box

1 x GigaCore 16RFO


1 x Quick Start Guide (including warranty information and safety instructions).

2 x Neutrik PowerCon TrueOne female connector

Description

Front panel


The GigaCore 16RFO offers several different fibre port configuration. Your configuration may differ from the one detailed below. This configuration is used as a reference only.



- 10 x 10/100/1000Mbps shielded Neutrik Ethercon connector
- 4 x slots for D type rugged fibre connectors
- 4 x LED for switch status
- 3 x LED per port for Ethercon front port status
- 2 x LED per port for Ethercon and fiber port status
- 1 x display
- 1 x Jog

* : Available in a future firmware release

Rear panel



- 2 x 10/100/1000Mbps shielded Neutrik Ethercon connector
- 4 x slots for D type rugged fibre connectors
- 1 x Serial console port on RJ45
- 2 x Redundant fan (on the side of the unit). In the unlikely of a fan failure, the other fan will switch to 100%, so one fan can manage the cooling of the unit. Fans run at a minimum of 30%
- 2 x Neutrik PowerCon True1 IN/OUT connector

Led indicators

The LED indicators of the GigaCore 16RFO include status, Poe, RlinkX, power, link/speed. The following shows the LED indicators for the GigaCore 16RFO along with an explanation of each indicator.

Switch LED		Status	Meaning
OK (General status LED)		Green	All OK
		Red blink	Unit is booting / Unit is flashing firmware / Unit is writing the flash memory.
PoE LED		Off	No PoE
		Green	Internal and external PoE supply OK
		Orange	Internal supply OK (no external supply available)
		Red blink	Error
RlinkX LED			Available in a future release
Power LED		Off	No Power
		Green	Internal and external power supply OK
		Orange	Internal power supply OK (no external supply available)
		Red blink	Error
Port LED		Status	Meaning
PoE LED		On	Sourcing
		Off	Not sourcing
		Blink	Error
RlinkX LED	SFP	On	Redundant port / link
Link	SFP	Off	No link
		Green	Gigabit connection
		Orange	10/100 Mbps connection
		Blink	Activity

Display

The front end display actually offers basic information about the switch configuration. A sequence of screens show the following information:

- Name
- Type of the device
- Ip address
- Netmask


Please find herein the menu hierarchy :

*Note: The IP address set in DHCP mode is set for backup purpose. If no DHCP server is discovered at boot-up, the switch will automatically use the assigned IP address.

The front end display offers basic information and configuration of the GigaCore 16RFO, such as network settings, ports info and groups assignment.

Please find below the flowchart of the menu:

- Press
- Press & Hold
- ⦿ Press & Hold, turn left
- ⦿ Press & Hold, turn right
- <> left & right navigation



Starting

The device operates with an AC voltage between 100V and 240VAC within a frequency range of 50Hz to 60Hz. Two Neutrik PowerCon TrueOne chassis are located at the rear of the unit. Please use the attached Neutrik Powercon TrueOne female connectors to feed power to the unit. Luminex recommends to use a power cable in accordance with the standards and the relevant authorities of your country.



!!! WARNING: TO ENSURE A TOTAL PROTECTION, THIS EQUIPMENT MUST BE EARTHED !!!

Assembly instructions

A Insert cable into the bushing and housing.
Note: "Apply cable pulling lubricant to cable jacket."
 40 - 50 mm

B Separate the housing from the bushing (cable remain in bushing)

C Place chuck over the cable.

D Prepare cable as shown.

VDE (EN 60320-1/EN60320-2-2)	UL (UL 498 / CSA C22.2 No. 182.3)
-------------------------------	------------------------------------

E

Torx size T8
 Torque Value 0.7 Nm

Slide the cable into the contacts and clamp with the screw with Torx size T8.

Wiring	VDE	UL
L	brown	black
N	blue	white
⊥	green/yellow	green

F

Important: Push and turn simultaneously.

Slide chuck onto insert (1) and then both into housing (2).
Important: Align the chuck by positioning the nose into keyway.

Connect the power cable to the device, and connect the other side of the cable to the mains. It will take around 20 seconds for the switch to boot up. Your GigaCore 16RFO is now ready to use.

Specifications

Power Input		Physical	
Power Input	100-240VAC - 50/60Hz 0.3A - 0.125A 1.8A - 0.75A with PoE Option	Enclosure	Metal Housing
		Dimensions (W x D x H)	482 x 294.15 x 48.45 mm 19" x 11.58" x 3.48"
Backup Power Input	100-240VAC - 50/60Hz 0.3A - 0.125A 1.8A - 0.75A with PoE Option	Packaging	510 x 410 x 136 mm 20.07" x 16.14" x 5.35"
		Weight	4.9Kg
Fuse	3.15A 250V Slow Blow	Approvals	
Environmental		CE	✓
Operating Temperature	0 to + 50°C	EN 55103-1	✓
Storage temperature	-10 to +70°C	EN 55103-2	✓
Humidity	5 to 95 % RH	EN 60950-1	✓
		RoHS Compliance	✓

Luminex LCE operates a policy of continuous development. Luminex LCE reserves the right to make changes and improvements to any of the products described in this document above without prior notice. Specifications are subject to change without notice.

Connection to the web interface

- Connect a computer to the switch.
- Set an IP address in the same range as the switch IP address.
- Default GigaCore IP address is displayed at the rear of the unit. Set your computer with a compliant IP address (do not use the same IP address !). IP address is also available on the front display.
- Launch your favorite web browser.
- Type the IP address of the switch in the address field.
- Enter admin in the login field. Leave the password field blank.

Additional documentation

All additional documenttion can be downloaded from our web pages in the support section :

<http://www.luminex.be>

--> Support

Luminex
Network Intelligence

Berkennlaan 8A
3940 Hechtel Eksel
Belgium
tel: +32 11 812 189
info@luminex.Be
www.luminex.be